

Scan For
PDF CATALOGUE



VOGUE

FLUTED ACRYLIC LAMINATE

VOGUE

FLUTED ACRYLIC LAMINATE



ADITI GRAPHICS 98981 53703

Feel
FANTASTIC

FLUTED ACRYLIC LAMINATE

2.5mm
100% ACRYLIC

6H HARDNESS
ANTI SCRATCH | ANTI YELLOW

VOGUE

FLUTED ACRYLIC LAMINATE


Vogue having best in class aesthetics feature under this head. Drafted using state of the art technology, these Laminates come with an assurance of durability and long term surface finesse. They can lift the mood of any and every type of ambiance



Feel
FANTASTIC

FLUTED ACRYLIC LAMINATE

PRODUCT FEATURES



HIGH GLOSS FINISH



EASY TO CLEAN




ANTI BACTERIAL SURFACE



SCRATCH RESISTANCE




STAIN RESISTANCE




100 % PURE ACRYLIC

SHEET SIZE : 2440x1220 mm | THICKNESS : 2.5mm SOLID


**ACRYLIC
LAMINATE**
ANTI YELLOW




VC-2171



VC-2172



VC-2111




VC-2112




SHEET SIZE : 2440x1220 mm | THICKNESS : 2.5mm SOLID


ACRYLIC LAMINATE
ANTI YELLOW



VC-2173



VC-2174



VC-2114




VC-2116






SHEET SIZE : 2440x1220 mm | THICKNESS : 2.5mm SOLID

ACRYLIC
LAMINATE
ANTI YELLOW




VC-2175



VC-2176




VC-2131




VC-2128





VC-2177



VC-2178



VC-2124



VC-2132






VC-2180

VC-2179




SHEET SIZE : 2440x1220 mm | THICKNESS : 2.5mm SOLID

**ACRYLIC
LAMINATE**
ANTI YELLOW



VC-2179



VC-2180



VC-2133



VC-2136




SHEET SIZE : 2440x1220 mm | **THICKNESS :** 2.5mm SOLID

**ACRYLIC
LAMINATE**
ANTI YELLOW



VC-2181



VC-2182



VC-2135



VC-2118




VC-2183


VC-2138

SHEET SIZE : 2440x1220 mm | THICKNESS : 2.5mm SOLID

ACRYLIC LAMINATE
ANTI YELLOW



VC-2183



VC-2184



VC-2138




VC-2139






VC-2185



VC-2185



VC-2186





VC-2187



Scan QR Code
Product Full View



VC-2188



Scan QR Code
Product Full View



SHEET SIZE : 2440x1220 mm | THICKNESS : 2.5mm SOLID

ACRYLIC LAMINATE
ANTI YELLOW



VC-2189



Scan QR Code
Product Full View




VC-2190



Scan QR Code
Product Full View



VC-2141









VC-2142








Parameter	Acrylic Laminate	High Gloss Laminate Mica	PU Coating/ Duco Paint	Back Painted Glass
Gloss Level	>90	>70	>85	>85
Scratch Proof	6H Anti Scratch	No	No	No
Color Consistency	Excellent	Not Good	Not Good	Not Good
Orange Peel	No	Yes	Yes	No
UV Resistance	Excellent	Bad	Bad	Bad
Water Resistance	Excellent	Bad	Bad	Excellent
Dry Heat Resistance	Excellent	Good	Bad	Bad
Volatile Organic Compounds (VOCs)	No	Yes	Yes	Yes

Reasons For Air Bubble Formations On Laminates:

-  Laminates Are Bonded In Extremely Humid Conditions
-  Use of water base synthetic resin adhesive any other than PEVA (Polyethylene Vinyl Acetate Co-polymer)
-  When Substrate Loses Moisture After Installation.
-  Debonding In Certain Areas Because Of Uneven Substrate Surface
-  Use Of Extremely Large Acrylic/pvc Laminate Sheets (more Than 8 Ft X 2ft Long)
-  Insufficient Or Lack Of Pressing During The Bonding Period Of Laminate

Causes Of Yellow Patches And Colour Fading After Installation:

-  Exposure To Direct Sunlight Can Gravelly Affect A Laminate's Appearance
-  Use Of Inferior Or Sub-standard Dipped Plywood Or Dipped Lipping Patti, Which May Chemically React With The Adhesive
-  The Use Of Synthetic Rubber Adhesives Such As Sr / Jat Pat, Bostic, Heatx, Etc.
-  Prolonged Exposure To High Temperature (above 30°C-35°C)
-  If Hot Cookware Or Utensils Are Directly Placed On The Laminate

The Company Is Not Responsible For Any Kind Of Complains Regarding Damage Of The Furniture For Laminates. The Resins Seen Here Can Have Many Possibilities Like Inferior Quality Of Plywood, Any Mistake While Using It. The Company Is Responsible Only Till The Sheet Is Not Used.

HOW TO CARE

- Cleaning Should Be Done With Water And Clean, Non-abrasive Cloth.
- To Remove More Stubborn Stain, Use Mild Household Cleansers Like Colin To Gently Wipe Down With A Non-abrasive Cloth.
- Avoid The Use Of Abrasive Liquid Cleanser's, Bleaching Compounds Or Solutions As These May Damage The Surface Of The Laminate.
- Do Not Place Hot Cookware Directly On The Laminate. Prolonged Exposure To Temperature Above 30 Degrees Celsius May Cause Damage To The Laminate Surface.
- Do Not Use The Laminate For Purposes That It Is Not Intended For (E.g. Do Not Iron Chop, Hammer Or Expose The Laminate To Open Flame)
- Outdoor Application Of The Laminate With Exposure To Direct Sunlight And Conditions Are Not Recommended.
- UV Rays May Be Shaping The Laminate.
- Gloss Surface Are Recommended Only For Vertical Application.
- Peel Off The Protective Film After Processing.
- Have A Thickness Balance Of $\pm 0\%$

LIMITED WARRANTY

Products Are Tested To Be Reasonably Free Of Defects, And When Used And Fabricated Properly They Will Comply With The Applicable Manufacturing Specifications Within Realistic Deviations. We Recommend Customers To Inspect Properly Before Installing. VOGUE Warranty In On Way Covers Defects And Non-compliance Or Otherwise Attributable To Any Other Causes, Including Without Limitation The Following:

- Improper Handling / Transportation / Storage.
- There Will Be No Guarantee Or Exchange Under Any Circumstances Improper Installation.
- Color Variations In Products From Different Batches Are Possible.
- Improper Or Unintended Usage.
- We Recommend Using Products From Same Batch To Avoid Color Variations.
- lack Of Or Improper Maintenance.
- This Brochure Is For Presentation Purpose Only.
- Exposure To High Temperatures.
- Unauthorized Alteration To The Products.
- Outdoor Applications.
- Exposure To Direct Sunlight Can Gravelly Affect A Laminate's Appearance.
- Use Interior Or Sub-standard Dipped Plywood Or Dipped Lipping Patti, which May Chemically React The Adhesive.
- The Use Of Synthetic Rubber Adhesives Such As Sr / Jat Pat, Bostic, Heatx, Etc.
- Prolonged Exposure To High Temperature (above 30°C-35°C).
- If Hot Cookware Or Utensils Are Directly Placed On The Laminate.
- To Avoid The Inside Cracks & Stretch Line, Do Not Store Acrylic Sheet In Roll From.

DISCLAIMER

- Do Not Use Plywood With High Moisture Content.
- Do Not Use Ply With Uneven Surface.
- Avoid Using Interior Quality Adhesive.
- Apply Sufficient Pressure.
- We Do Not Recommend Pasting Of Sheets On The Printed/branding Area Of The Plywood.

There Can Be Colour Variation From Different Batches. It Is Advised To Use Same Batch Material To Avoid Colour Variations. Actual Colour Of The Acrylic Sheet May Vary From This Brochure.